

MK-04B black/MK-04W white

previously MK-01/MK-02



- Hands-free monitor
- 7" panoramic color screen TFT LCD 640×480;
- Support for 2 door stations (or 1 station + 1 CCTV camera)
- Electric door strike and automatic door control
- The module can be expanded by 3 additional, randomly selected monitors or uniphones (except MK-10 series monitors)
- Adjustment of monitor parameters (volume, brightness and color)
- Color of the housing:
MK-04B – black
MK-04W – white
- Movable buttons
- Wiring: 4+2 for bolt + 2 for gate
- Power supply: 14.5 V DC
- Power supply for DIN rail included
- Dimensions: 245×160×18 mm

MK-03 black/MK-03W white



- Hands-free monitor
- 7" panoramic color screen TFT LCD 640×480
- Touch, backlit control panel (backlight color - blue)
- Support for 2 door stations (or 1 station + 1 CCTV camera)
- Electric door strike and automatic door control;
- The module can be expanded by 3 additional, randomly selected monitors or uniphones (except MK-10 series monitors);
- Intercom and call forwarding
- Adjustment of monitor parameters (ringtone volume, talk volume, brightness, and color)
- Color of the housing:
MK-03 – black
MK-03W – white
- Preview with the ability to enable sound and open the door
- Power supply: 14.5 V DC
- Power supply for DIN rail included
- Installation: 4+2 for bolt + 2 for gate
- Dimensions: 241×161×23 mm

Uniphones

MU-01 headset



- Electric door strike control
- The module can be expanded by additional MU-01 or MU-02 uniphones or any monitors (except MK-10 series monitors)
- Intercom function
- Adapted to control a low-current 12 V DC electric door strike without the need for an additional transformer
- Installation: 3-wire + 2 for bolt (for stand-alone installation) 3 + power supply, as additional for the monitor
- Dimensions: 90×200×50 mm

MU-02 hands-free



- Electric door strike control
- The module can be expanded by additional MU-01 or MU-02 uniphones or any monitors (except MK-10 series monitors)
- Call forwarding feature
- Adapted to control a low-current 12 V DC electric door strike without the need for an additional transformer.
- Installation: 3-wire + 2 for bolt (for stand-alone installation) 3 + power supply, as additional for the monitor
- Surface mounting
- Dimensions: 160×120×42 mm

Application

Uniphones work with all types of monitors.